

MAX 161















The MAX® Series of Welding Inverters, developed from STEL INVERTER TECHNOLOGY, concentrates a high excellence of welding performance in a portable lightweight compact structure.

With an operator-freindly easy to read front panel design, the selection of the correct parameter for each electrode diameter is immediate and uncomplicated.





MAIN FEATURES



3,25MM ELECTRODE

Owing to the Inverter technology from Stel, the MAX® 161 is capable of welding 3,25mm electrodes.



LIGHTWEIGHT

Maximum portability due to low weight and practicle structure design, makes the MAX® 161 ideally suited for site work and any workshop.



FLY-BACK

Advance dynamic electronic system of auxiliary input voltage (not traditional transformer) masters total control from all input power source voltages automatically.



TIG SCRATCH

Using a Tig Torch with gas-valve, the MAX® 161 can perform excellent DC TIG welding with scratch ignition.





Technical Data	MAX® 161
Main Voltage	230/240 V
Phase	1
Frequency	50/60 Hz
Real Current (30%)	16 A
Real Power (30%)	3,8 KVA
Power Factor	0,8
No Load Voltage	75V
Current Range	5-150 A
Welding Current 45% (25°C)	150 A
Welding Current 100% (25°C)	100 A
Welding Current 30% (40°C)	150 A
Welding Current 60% (40°C)	100 A
Welding Current 100% (40°C)	95 A

Features	MAX® 161
Earth Clamp	16 mm²
Degree of Protection	IP 23
Insulation Class	Н
Cooling	Air
Work Temperature	40°C
Length/Width/Height (mm)	330x135x270
Weight	5,5 Kg

The date is measured at an environment temperature of 40 $^{\circ}\text{C}$

Main Accessories



WELDING KIT 16mm²

- Earth Cable 2m 16mm² Rubber
- Cable/Electrode Holder 3m 16mm² Rubber
- Wire Brush/Chipping Hammer+Handscreen Cod. 6083600010



CABLES KIT 16mm²

- Earth Cable 2m 16mm² Rubber
- Cable/Electrode Holder 3m 16mm² Rubber

Cod. 601039000L



HELMET MEGA 600S

Large viewing area for maximun vision featuring innovative adjustments of delay, sensitivity and DIN protection, Shade 9-13. Cod. 601253000L



STEL BAG

Portable and easy to use the Max can be used by anyone...anywhere!

Cod. 6011410000



TIG TORCH 17V Tig Torch with valve.

Tig Torch 17V 4m Air Cod. 642830000L Tig Torch 17V 8m Air Cod. 642840000L